



parallel speaker cables

- cable with separable conductor pair, standard cable for speaker connections used with banana plugs or screw-type connectors / 0.75–6.0 mm²

PVC

Parallel loudspeaker cables suit very well in installations. Easily dividable conductors can be attached to connectors or screw type terminals at cabinets or amplifiers very quickly. The HiFi market often uses this parallel cable with its transparent PVC jacket because of the high number of strands and low resistance values.

construction

conductor **stranded bare copper**
 outer jacket **PVC**

working temperature installed **-30°C / +70°C**
 moved **-10°C / +70°C**

electric

insulation resistance **20 MΩ x km**
 test voltage **1 V**
 max. operating voltage **50/75 V AC/DC**

order code	cond. cross section mm ²	cond. construction mm	conductor resistance Ω/km	dimensions mm	color	weight kg/m	standard lengths m
LYP007S	0.75	24 x 0.20	26	2.35 x 4.9	black	0.02	15 / 30 / 50 / 100 / 500
LYP007T	0.75	24 x 0.20	26	2.35 x 4.9	transparent	0.02	15 / 30 / 50 / 100 / 500
LYP007W	0.75	24 x 0.20	26	2.35 x 4.9	white	0.02	15 / 30 / 50 / 100 / 500
LYP015S	1.5	48 x 0.2	13.3	2.8 x 5.8	black	0.04	15 / 30 / 50 / 100 / 500
LYP015T	1.5	48 x 0.2	13.3	2.8 x 5.8	transparent	0.04	15 / 30 / 50 / 100 / 500
LYP015W	1.5	48 x 0.2	13.3	2.8 x 5.8	white	0.04	15 / 30 / 50 / 100 / 500
LYP025S	2.5	78 x 0.2	7.98	3.6 x 7.4	black	0.06	15 / 30 / 50 / 100 / 500
LYP025T	2.5	78 x 0.2	7.98	3.6 x 7.4	transparent	0.06	15 / 30 / 50 / 100 / 500
LYP025W	2.5	78 x 0.2	7.98	3.6 x 7.4	white	0.06	15 / 30 / 50 / 100 / 500
LYP060T	6.0	189 x 0.2	3.3	6.1 x 12.5	transparent	0.14	15 / 30 / 50 / 100

technical specifications are subject to change