

INTRODUCTION

The 1x4 HDMI Splitter distributes 1 HDMI source to 4 HDMI displays simultaneously. Adapt to a variety of complex application environments and enhance device compatibility. It offers HD video solution for super market, shopping mall, HDTV/STB/DVD/Projector/DVB factory, data control center, information distribution, conference room presentation, education and training, corporation showroom, luxurious house etc.

FEATURES

- 1 HDMI input signal split to 4 HDMI sink devices.
- 3D HDMI 1.4a video format support, HDCP 1.4 protocol compliant.
- 3D video support including frame packing for all 3D formats up to a 297MHz TMDS clock.
- Support deep color 30bit, 36bit, 48bit per pixel.
- Digital audio format, as DTS-HD/Dolby-true-HD/LPCM 7.1/DTS/Dolby-AC3/DSD.

PACKING LIST

- HDMI Splitter 1pc
- Power Adapter 1pc
- User Manual 1pc

SPECIFICATIONS

Video	Protocol	HDMI 1.4; HDCP 1.4
	HDMI Pixel bandwidth	225MHz
	HDMI interface bandwidth	Total bandwidth 10.2Gbps
	Highest Resolution	3840*2160@30Hz; 4k@60Hz (4:2:0)
	Connector	HDMI-A
	HDMI interface Impedance	100*
	HDMI cables	1920X1080@60Hz<5m
	Power Supply	DC 5V
	Power Consumption	MAX 4W
	Operating Temperature	-5'C~ +70'C
	Relative Humidity	5%~90%
	Size	120*55*19mm
	Warranty	1 year warranty